Belshaw.

Product Line **PLUNGERS & CYLINDERS**

Models

Type B & F Depositors

Туре В & F	Part Number	Plunger / Attachment	Plunger	Donut Type
1-1/2" Plunger Diameter	7SSx1-1/2	PLAIN RING For standard Ring donuts. Also makes		00
1-3/4" Plunger Diameter	7SSx1-3/4			
1-7/8" Plunger Diameter	7SSx1-7/8	"Old Fashion" donuts using Old Fashion donut mix.		
2" Plunger Diameter	7SSx2			
1-3/4" Plunger Diameter	7SC-SSx1-3/4	STAR RING		\bigcirc
1-7/8" Plunger Diameter	7SC-SSx1-7/8	For Ring donuts with a star pattern around the center hole.		
2" Plunger Diameter	7SC-SSx2			
1-5/8" Plunger Diameter	7B-1009x1-5/8	FRENCH CRULLER	and the second sec	
1-7/8" Plunger Diameter	7B-1009x1-7/8	Use with French Cruller mix to make French Crullers. Use with standard cake donut mix to make		
2" Plunger Diameter	7B-1009x2	"French Cake" donuts.		
1-3/4" Plunger Diameter	7F-1004x1-3/4	KRINKLE / MOCHI		
1-7/8" Plunger Diameter	7F-1004x1-7/8	 Features eight distinctive ball shaped sections all joined together.Sometimes known as Pon-de-Ring.Commonly used 		
2" Plunger Diameter	7F-1004x2	to make Mochi donuts. (need submerger)		
1-3/4" Plunger Diameter, 4 holes - 5/8" holes	7G-1000-084B			
1-3/4" Plunger Diameter, 3 holes - 3/4" holes	/G-1000-083C	BALL		
1-7/8" Plunger Diameter, 4 holes - 5/8" holes	7G-1000-094B	 Produced ball shaped donuts or donut holes. With a compatible mix recipe, 		
2" Plunger Diameter, 4 holes - 5/8" holes	7G-1000-104B	can also make other products such as hushpuppies, loukoumades, falafel,		
2" Plunger Diameter, 2 holes - 7/8" holes	7G-1000-102D	African Puff Puff, and more. (need submerger)		
2" Plunger Diameter, 3 holes - 1" holes	7G-1000-103E			
2" Plunger Diameter, 3 holes - 3/4" holes	7G-1000-103C	Typically used for Loukoumades		
2" Plunger Diameter, 3 holes - 7/8" x 1" oblong holes	7G-1000-103DB	Typlically used for Hushpuppies		222
2" Plunger Diameter, 1 slot - 1/4" x 1-1/4" slot	7H-1000-101DG (makes 1)	STICK Makes 1 or 2 stick donuts. The thickness		
2" Plunger Diameter, 2 slots - 1/4" x 5/8" slots	7H-1001-082DB (makes 2)	 of the donut will depend on the size of the slot and the length will depend on the dial setting for the depositor. 	No.	and the second s
2" Plunger Diameter with "Star" pattern hole	7CD-1009X2	CHURRO For churros 2 to 6 inches long. (need submerger)		
Cylinder Ite	m Numbers	Description	·	Cylinder
003	35SSAx1-1/2 35SSAx1-5/8 35SSAx1-3/4	Plunger size and cylinder size must ma For example, a 1-3/4" plunger must always be used with a 1-3/4" cylinder.	You	
	35SSBx1-7/8 35SSBx2	can use various plungers with a single cylinder, of the same size.		

NOTES - 1. Other sizes may be special ordered



Belshaw

PLUNGERS & CYLINDERS Product Line

Type B & F Depositors Models

ACCESSORIES FOR TYPE B & TYPE F CAKE DONUT DEPOSITORS

Column Mount Bracket Kit

The Column Mount attaches to the side of the fryer and supports Type B, and F depositors. Fryer must be bolted to the floor. The full extension of the column mount is 42"/105cm, from the column to the donut drop.

Part #0405 (for Type B and Type F), Part #P-1000 (Bracket Plate Kit, for non-Belshaw fryers)





Wall Mount Bracket Kit

The wall mount supports Type B or F cake donut depositors, with precision screw for adjusting the angle of the depositor. Mounts to the wall behind or alongside fryer. Maximum extension 42"/105cm from wall to donut drop.

Item Nbr #0406

Bracket Arm Height Adjuster

The Bracket Arm Height Adjuster precisely adjusts the height of your Type B and F depositor. The large turn screw adjustment is faster and more accurate than the Set Collar supplied with the standard mounting kits. Useful when making more than one type of cake donut requiring quick change between different drop heights. For column mount only.

Part #0400

Hopper

Replacement aluminum hopper for Type B and Type F. Capacity 15 lbs (6.8 kg). Accepts Belshaw B and F Plungers and Cylindersinto bottom opening.

Part #0290

Plungers and Cylinders

A variety of plungers and cylinders are available for Type B and F depositors. (See reverse page for details)

APPROXIMATE RING DONUT WEIGHTS

Plunger Size		Product Weight (per dozen, after frying)		
in	mm	min	max	
1″	25.4mm	5oz. (142g)	8oz. (227g)	
1-1/2"	38.1mm	12oz. (340g)	15oz. (425g)	
1-3/4″	44.5mm	16oz. (454g)	20oz. (567g)	
1-7/8″	47.6mm	19oz. (539g)	24oz. (680g)	
2″	50.8mm	22oz. (624g)	27oz. (765g)	





Bracket arm height adjuster

Hopper

Plungers and cylinders







111