

## BX10 Eco-touch Bakery Convection Oven with 4-Shelf Stand *(sold separately)*

### OVEN FEATURES

- Holds ten 18" x 26" baking pans
- 3½" height between pan shelves
- Steam injection standard on all ovens
- Touchscreen graphical controller (see features below)
- High quality build with rigid foil-faced insulation around oven
- Bi-directional fan (for more even baking)
- Welded seams throughout, to prevent steam leakage into insulation layer around oven
- Cool-to-Touch double insulated door with twin pane viewing window
- Certified to ETL and NSF

### COLOR TOUCH SCREEN

- Touch screen controller for fast, easy, and mistake-free usage. Icons and illustrations used for menu selection.
- Up to 240 bake programs. Settings can be changed while the program is running. Each program has the option to control:
  - Bake time
  - Bake temperature
  - Steam duration
  - Damper open/shut (allows steam/heat to exit chamber)
  - Fan direction
- Most used programs can be stored in the favorites menu
- 7-day timer to start oven at selected times, ready for every shift. 4 events can be programmed for each day of the week.
- Help function at top of every screen
- Sleep mode returns oven to a selected standby temperature - reducing energy consumption up to 66%
- Auto-shutdown to prevent oven from being left on by mistake
- Diagnostics function to monitor performance, while oven is running
- Prompts such as "Door Open", "Bake Over", etc available as desired. (Standard alert tones and buzzers are also available)
- Baking programs are easily uploadable and downloadable via USB. This includes recipes, sounds and tones, logos, icons, images and software.



BX10 Eco-touch convection oven with 4-shelf stand. (sold separately)  
Shown with baguette trays (purchased separately).

## SPECIFICATIONS

### EACH OVEN REQUIRES 2 ELECTRICAL CONNECTIONS AND 1 WATER CONNECTION

Pan size	18" x 26"
Shelf spacing - Oven (10 shelves)	3.5" per shelf

### SHIPPING DATA (approximate)

Shipping weight	840 lbs
-----------------	---------

### ELECTRICAL CONNECTION

Volts	208 V, 60 Hertz, 3 phase
Amps	45 A
Connection	Hard wired, 1-1/4" seal flex (3C+G)
Cord	72 inches

### WATER CONNECTION

Pressure	20 psi
Connection	Garden hose thread connection
Damper	Butterfly type

### CLEARANCE REQUIREMENT

Clearance requirement	2" at rear
-----------------------	------------

### CERTIFICATIONS

ETL certified to ETL and NSF
------------------------------

BX Eco-touch Controller (sample screens)

